


SHOWN IN DE-ENERGIZED POSITION



JFW INDUSTRIES, INC.
INDIANAPOLIS, IN

PROPRIETARY INFORMATION
ALL SURFACES ARE TO BE FREE
OF BURRS, PITS, & SCRATCHES

MODEL#	A	B	C	D
50P-847, 50P-1039	1dB	2dB	4dB	8dB
50P-1729	2dB	4dB	8dB	16dB
50P-829	5dB	10dB	20dB	20dB
50P-883	10dB	20dB	30dB	30dB
50P-788, 50P-1516 50P-758, 50P-766	10dB	20dB	20dB	20dB

REV	ECN	DATE	BY	DRAWN BY	M. HUFF	DATE	2 OCT 90
A	3332	24JUL91	TEZ	APP'D BY		SCALE	FULL
B	3430	03OCT91	TEZ	MATERIAL	ALUMINUM ALLOY		
C	3610	21APR92	TEZ	FINISH	ELECTROLESS NICKEL		
D	4136	24JAN94	TEZ	DESCRIPTION	4 STEP PROGRAMMABLE ATTENUATOR		
E	4205	06APR94	TEZ				
F	6912	27NOV01	MAH				
G	7011	13FEB02	MAH				
H	12897	6-7-06	BZ				

TOLERANCES
FRACTIONAL DIM. ± 1/64
2 PLACE DECIMAL ± .010
3 PLACE DECIMAL ± .005
ANGULAR DIM. ± 1/2°
DWG NO. 092-1559