SPECIFICATION SHEET

JFW MODEL 50PM-011

MAKE BEFORE BREAK PANEL MOUNTED ROTOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-1000 MHz
Impedance	50 Ohms nominal
Attenuation Range	0-81 dB in 0.1 dB steps
VSWR	1.3:1 maximum DC-500 MHz 1.5:1 maximum 500-1000 MHz
Attenuation Accuracy	DC-500 MHz ± 0.04 dB (0.1 dB steps) ± 0.2 dB (1 dB steps) ± 0.7 dB (10 dB steps) 500-1000 MHz ± 0.06 dB (0.1 dB steps) ± 0.3 dB (1 dB steps) ± 1.0 dB (10 dB steps)
RF Input Power	1 Watt average
Insertion Loss	2.0 dB maximum 1.6 dB typical @ 1000 MHz
RF Connector	SMA, BNC, TNC, or N female
Physical Size	See outline drawing 092-1968

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	11/06/1995						
9999	08/14/2003	A	TRS 03/15/2010				
18498	04/05/2010	B	TRS 04/05/2010				