

SPECIFICATION SHEET

JFW MODEL 50PM-059

PANEL MOUNTED ROTOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-2700 MHz
Configuration	2 panel mounted rotary attenuators (specifications are for each individual rotor)
Impedance	50 Ohms nominal
Attenuation Range	0-60 dB in 1 dB steps
VSWR	1.35:1 maximum DC-1000 MHz 1.5:1 maximum 1000-2700 MHz
Insertion Loss	0.6 dB maximum DC-1000 MHz 1.2 dB maximum 1000-2700 MHz
Attenuation Accuracy	± 0.5 dB or 3%
RF Input Power	2 Watts average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	30° with stops at minimum and maximum
RF Connector	SMA or N female
Operating Temperature Range	-20°C to +85°C
Physical Size	See outline drawing 092-6187-01

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	05/19/2009		TRS 05/19/2009				
17278	06/03/2009	A	TRS 06/03/2009				