


DETAIL A  
3M# 3793-5303

PIN	FUNCTION
1	CONTROL 1
2	NO CONNECTION
3	CONTROL 2
4	NO CONNECTION
5	CONTROL 3
6	+5 Vdc
7	CONTROL 4
8	-5 Vdc
9	NO CONNECTION
10	GROUND

J13 TO:	C1	C2	C3	C4
NONE	0	0	0	0
J1	1	0	0	0
J2	0	1	0	0
J3	1	1	0	0
J4	0	0	1	0
J5	1	0	1	0
J6	0	1	1	0
J7	1	1	1	0
J8	0	0	0	1
J9	1	0	0	1
J10	0	1	0	1
J11	1	1	0	1
J12	0	0	1	1

 <b>JFW INDUSTRIES, INC.</b> INDIANAPOLIS, IN						PROPRIETARY INFORMATION		
REV	ECN	DATE	BY	DRAWN BY	CDJ	DATE	1-10-97	ALL SURFACES ARE TO BE FREE OF BURRS, PITS, & SCRATCHES
A	5191	1-31-97	TEZ	APP'D BY		SCALE	1/2	TOLERANCES
B	5398	9-18-97	TEZ					FRACTIONAL DIM. ± 1/64
C	5401	9-19-97	CDJ	MATERIAL	ALUMINUM ALLOY			2 PLACE DECIMAL ± .010
D	6989	1-28-01	CMB	FINISH	NICKEL			3 PLACE DECIMAL ± .005
				DESCRIPTION	50S-XXX: 1P12T SWITCH			ANGULAR DIM. ± 1/2°
								DWG NO. 092-2531