



DETAIL A
3M# 3793-5303

PIN	FUNCTION
1	CONTROL 1
2	NO CONNECTION
3	CONTROL 2
4	NO CONNECTION
5	CONTROL 3
6	+5 Vdc
7	CONTROL 4
8	+24 Vdc
9	NO CONNECTION
10	GROUND

J13 TO:	C1	C2	C3	C4
NONE	0	0	0	0
J1	1	0	0	0
J2	0	1	0	0
J3	1	1	0	0
J4	0	0	1	0
J5	1	0	1	0
J6	0	1	1	0
J7	1	1	1	0
J8	0	0	0	1
J9	1	0	0	1
J10	0	1	0	1
J11	1	1	0	1
J12	0	0	1	1

SMA FEMALE
13-PLACES

DETAIL A



				JFW INDUSTRIES, INC. INDIANAPOLIS, IN		PROPRIETARY INFORMATION	
						ALL SURFACES ARE TO BE FREE OF BURRS, PITS, & SCRATCHES	
REV	ECN	DATE	BY	DRAWN BY	B. ZEIHEN	DATE	1-5-04
A	7748	2-18-04	TEZ	APP'D BY		SCALE	1/2
				MATERIAL	ALUMINUM ALLOY		TOLERANCES
				FINISH	NICKEL		FRACTIONAL DIM. ± 1/64
				DESCRIPTION	50S-XXXX: 1P12T SWITCH		2 PLACE DECIMAL ± .010
							3 PLACE DECIMAL ± .005
							ANGULAR DIM. ± 1/2°
							DWG NO. 092-4368