

SPECIFICATION SHEET

JFW MODEL 50S-1567

1P12T SELF TERMINATING SOLID STATE RF SWITCH

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	20-4300 MHz
Configuration	1P12T Self Terminating
Impedance	50 Ohms nominal
VSWR	1.6:1 maximum
Insertion Loss	2.0 dB maximum 20-1000 MHz 2.5 dB maximum 1000-2000 MHz 3.5 dB maximum 2000-3000 MHz 4.5 dB maximum 3000-4000 MHz
Isolation	70 dB minimum to 2000 MHz 50 dB minimum to 4300 MHz
Switching Speed	20 microseconds
RF Input Power	+20 dBm (20-100 MHz) +30 dBm (100-4300 MHz)
Control Logic (4 Lines)	TTL per 092-4368
DC Supply	+24 Vdc @ 100 mA nominal and +5 Vdc @ 100 mA nominal
DC Connector	3M #3793-5303
RF Connector	SMA female
Operating Temperature Range	0°C to +70°C
Physical Size	See outline drawing 092-4368

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	08/28/2007		BAC 08/28/2007				