

SPECIFICATION SHEET
JFW MODEL 50T-473-XX
TERMINATION/MISMATCH

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

Frequency Range DC-1000 MHz

Impedance 50 Ohms nominal

VSWR 1.10:1 maximum (1.0:1)
 or
 ± 5% maximum (all mismatch values)

RF Input Power 5 Watts average @ 25°C

Peak Power 1000 Watts (1 microsecond)

RF Connector BNC, N, SMA, TNC, Reverse Polarity TNC
 or 7/16 (male or female)

Operating Temperature Range -40°C to +85°C

Physical Size See outline drawings:
 092-4403-01 (SMA male)
 092-4403-02 (SMA female)
 092-4403-03 (BNC male)
 092-4403-04 (BNC female)
 092-4403-05 (TNC male)
 092-4403-06 (TNC female)
 092-4403-07 (N male)
 092-4403-08 (N female)
 092-4403-09 (Rev. Polarity TNC male)
 092-4403-10 (Rev. Polarity TNC female)

XXX - Insert VSWR required (1.0, 1.1, 1.2, 1.5, 2.0, 2.5, 3.0, 3.5, 5.0, or 6.0). Other VSWR available upon request.

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	07/06/2007		TRS 07/06/2007				
14916	10/31/2007	A	SMR 10/31/2007				
20855	11/04/2011	B	TRS 11/04/2011				