

4-40 x  
.250 DP  
4-PLACES

1.687  
O.C.

.875  
O.C.

.28

.38

.34  
TYP.

.88

BNC FEMALE  
2-PLACES

2.00

1.19

75AP-018	0-10 Vdc	+5 Vdc
75AP-015	0-10 Vdc	+5 Vdc
50P-977	+12 Vdc	TTL CONT.
50AP-049	+6 TO +2 V	+5 Vdc
50P-930	+12 Vdc	+12 Vdc
75AP-001	0-15 Vdc	+5 Vdc
50AP-001	0-15 Vdc	+5 Vdc
50P-1467	+28Vdc	CMOS CONT.
MODEL #	PIN 1	PIN 2



**JFW INDUSTRIES, INC.**  
INDIANAPOLIS, IN

REV	ECN	DATE	BY	DRAWN BY	T. ZEISS	DATE	1-20-00
A	2351	2-8-89	TEZ	APP'D BY		SCALE	FULL
B	3745	9-21-92	PT	MATERIAL	BRASS		
C	3932	4-13-93	TEZ	FINISH	NICKEL		
D	4354	9-9-94	CDJ	DESCRIPTION	SEE CHART		
E	6169	1-20-00	TEZ				
F	6576	1-12-01	CMB				

PROPRIETARY INFORMATION
ALL SURFACES ARE TO BE FREE OF BURRS, PITS, & SCRATCHES
TOLERANCES
FRACTIONAL DIM. ± 1/64
2 PLACE DECIMAL ± .010
3 PLACE DECIMAL ± .005
ANGULAR DIM. ± 1/2°
DWG NO.
092-1116