

SPECIFICATION SHEET

JFW MODEL 75BR-014

BENCH TOP ROTARY ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-1000 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-90 dB in 1 dB steps
VSWR	1.3:1 maximum DC-500 MHz 1.5:1 maximum 500-1000 MHz
Attenuation Accuracy	DC-500 MHz ± 0.3 dB (0-10 dB) ± 0.5 dB (10-60 dB) ± 0.8 dB (70-90 dB) 500-1000 MHz ± 0.5 dB (0-10 dB) ± 1.0 dB (10-60 dB) ± 1.5 dB (70-90 dB)
Insertion Loss	1.0 dB maximum 0.75 dB typical @ 1000 MHz
RF Input Power	1 Watt average (1000 Watts peak)
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	BNC, F, or N female
Operating Temperature Range	-20°C to +85°C
Physical Size	See outline drawing 092-1266 (BNC)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
9999	05/15/2003	B	BAC 03/30/2004	20038	04/29/2011	E	TRS 04/29/2011
11130	05/05/2005	C	CLK 05/05/2005	20534	09/06/2011	F	TRS 09/06/2011
16299	09/09/2008	D	TRS 09/09/2008	20750	10/11/2011	G	TRS 10/11/2011