

**SPECIFICATION SHEET**

**JFW MODEL 75PM-006**

**PANEL MOUNTED ROTOR**

JFW Industries, Inc.  
Phone: 317-887-1340  
sales@jfwindustries.com  
www.jfwindustries.com

Configuration	2 panel mounted 75DR-009 rotary attenuators (specifications are for each individual rotor)
Frequency Range	DC-1000 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-70 dB in 1 dB steps
VSWR	1.4:1 maximum
Attenuation Accuracy	± 0.5 dB or 3%
Insertion Loss	0.75 dB maximum
RF Input Power	1 Watt average
Indexing	30 degrees with stops at minimum and maximum
Direction of Rotation	Attenuation increases in a Clockwise direction
RF Connector	BNC, F, or N female
Operating Temperature Range	-20°C to +85°C
Physical Size	See outline drawing 092-4082

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	10/16/2002		SL 10/16/2002	18504	04/06/2010	C	TRS 04/06/2010
4046	10/31/2002	A	CLV 10/31/2002				
14479	07/30/2007	B	TRS 07/30/2007				