


J17 TO	CONT.			
	1	2	3	4
J1	0	0	0	0
J2	1	0	0	0
J3	0	1	0	0
J4	1	1	0	0
J5	0	0	1	0
J6	1	0	1	0
J7	0	1	1	0
J8	1	1	1	0
J9	0	0	0	1
J10	1	0	0	1
J11	0	1	0	1
J12	1	1	0	1
J13	0	0	1	1
J14	1	0	1	1
J15	0	1	1	1
J16	1	1	1	1



DETAIL A

DE-9P

PIN	FUNCTION
1	CONTROL 1
2	CONTROL 2
3	CONTROL 3
4	CONTROL 4
5	NO CONNECTION
6	NO CONNECTION
7	NO CONNECTION
8	+12 Vdc
9	GROUND

NOTE : WITH NO POWER APPLIED TO DE-9 CONNECTOR
COMMON IS FAILSAFE CONNECTED TO J1

REV	ECN	DATE	BY	APPR	
-	ISSUED	6-22-90	CMB	PT	
A	17424	7-16-09	BZ	BAC	
B	20249	6-20-11	JZ	TEZ	
C	20928	11-28-11	JZ	TEZ	

MATERIAL	BRASS	PROPRIETARY INFORMATION
FINISH	NICKEL	ALL SURFACES ARE TO BE FREE OF BURRS, PITS, & SCRATCHES
MODEL	75S-XXX	TOLERANCES
DESCRIPTION	1P16T COAXIAL SWITCH	XXX-010 XXX-008 XXX-57
		DWG #
		092-3394

www.jfwindustries.com PH: 317-887-1340

SCALE 1/2