

SPECIFICATION SHEET

JFW MODEL 75SA-058

SWITCH ASSEMBLY

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	20-1000 MHz
Configuration	1P16T Self Terminating
Impedance	75 Ohms nominal
VSWR	1.6:1 maximum
Insertion Loss	2.5dB maximum
Isolation	55 dB minimum
RF Input Power	+20 dBm
Switching Speed	50 microseconds (after receipt of command and processing time. Typical processing time is 3 milliseconds)
Remote Control	Ethernet (TCP/IP, 10/100,4 users)
Control Connector	RJ-45 (Ethernet) DB-9P (Etherent config port)
Remote Commands	Command: Format: ----- Identify ID<cr> Set Switch SSx y<CR> Read Switch RSx<CR> x = Switch Number (1) Y = Port Number (0-16) <CR> = Carriage Return
AC Supply	85-264VAC @ 47-63 Hz
RF Connector	F female
Operating Temperature Range	0° to +50° C
Physical Size	See outline drawing 092-6808

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	12/03/2010		BAC 12/03/2010				