



CONNECTOR	DIM. A MAX.
SMA MALE	1.11
SMA FEMALE	1.00
BNC MALE	1.29
BNC FEMALE	1.35
TNC MALE	1.28
TNC FEMALE	1.35
N MALE	1.01
N FEMALE	1.10
7/16 MALE	2.02
7/16 FEMALE	1.94
4.1/9.5 MALE	.98
4.1/9.5 FEMALE	1.10
4.3/10 MALE	.98
4.3/10 FEMALE	1.16

* INSERT NOMINAL dB VALUE (0-30dB) i.e. 006 = 6dB

REV	ECN	DATE	BY	APPR
-	ISSUED	----	---	---
A	----	9-7-82	ST	FDW
B	2484	4-28-89	TEZ	FDW
C	2503	5-5-89	TEZ	FDW
D	3490	12-10-91	TEZ	PT
E	7038	3-14-02	MAH	TEZ
F	26009	12-15-15	JZ	TEZ
G	24444	9-5-19	GM	JZ



JFW INDUSTRIES, INC.

www.jfwindustries.com

PH: 317-887-1340

MATERIAL	ALUMINUM ALLOY	PROPRIETARY INFORMATION
FINISH	BLACK ANODIZE	ALL SURFACES ARE TO BE FREE OF BURRS, PITS & SCRATCHES
MODEL	50FH-XX [*] -10	TOLERANCES .XX±.010 .XXX±.005 XX°±.5°
DESCRIPTION	10 WATT FIXED ATTENUATOR	DWG # 092-128
SCALE	FULL	