

SPECIFICATION SHEET

JFW MODEL 50S-1313+XX-TTL

1P2T FAILSAFE REFLECTIVE ELECTROMECHANICAL RF SWITCH

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-18 GHz
Configuration	1P2T Failsafe Reflective
Impedance	50 Ohms nominal
VSWR	1.10:1 maximum DC-1GHz 1.15:1 maximum 1-4GHz 1.20:1 maximum 4-8GHz 1.30:1 maximum 8-12GHz 1.35:1 maximum 12-18GHz
Insertion Loss	0.10 dB maximum DC-1GHz 0.15 dB maximum 1-4GHz 0.20 dB maximum 4-8GHz 0.30 dB maximum 8-12GHz 0.35 dB maximum 12-18GHz
Isolation	85 dB minimum DC-1GHz 80 dB minimum 1-4GHz 70 dB minimum 4-8GHz 65 dB minimum 8-12GHz 60 dB minimum 12-18GHz
Switching Speed	15 milliseconds
RF Input Power (cold switched)	400 Watts average DC-200MHz 300 Watts average 200-500MHz 200 Watts average 500-1000MHz 100 Watts average 1-4GHz 90 Watts average 4-8GHz 70 Watts average 8-12GHz 60 Watts average 12-18GHz
DC Supply	+XX is either +12,+15,+24 or +28: ----- +12 Vdc(11-14Vdc)@ 200 mA nominal +15 Vdc(14-17Vdc)@ 160 mA nominal +24 Vdc(20-28Vdc)@ 120 mA nominal +28 Vdc(24-32Vdc)@ 100 mA nominal
Control (1 line)	TTL "low" (0-0.8Vdc) for COM to NC TTL "high" (2.0-5.5Vdc) for COM to NO TTL Current ±1.3mA maximum
Lifetime	1 million cycles minimum

--CONTINUED--

SPECIFICATION SHEET

JFW MODEL 50S-1313+XX-TTL

1P2T FAILSAFE REFLECTIVE ELECTROMECHANICAL RF SWITCH

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Weight 2.5 oz. Nominal
DC Connector Solder terminals
RF Connector SMA female
Operating Temperature Range -25°C to +65°C
Physical Size See outline drawing 092-4496
Add (-NR) for NON-RoHS version. (i.e. 50S-1313+12-TTL-NR SMA)



ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	08/18/2005		BAC 08/18/2005	19957	04/07/2011	C	TRS 04/07/2011
12568	03/24/2006	A	BAC 03/24/2006	33456	07/16/2024	D	TRS 07/16/2024
17644	09/02/2009	B	BAC 09/02/2009				