

SPECIFICATION SHEET
JFW MODEL 016-107-XX
CABLE ASSEMBLY

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

| | |
|-----------------|---|
| RF Connectors | SMA male to N male |
| Frequency Range | DC-3000 MHz |
| Impedance | 50 Ohms nominal |
| Cable Type | RG-402 |
| | Inner Conductor: 19 AWG silver coated copper-covered steel |
| | Outer Conductor: Copper-tin flexible composite braid with 100% shield coverage |
| VSWR | < 1.05:1 typical DC-500 MHz < 1.10:1 typical 500-1000 MHz < 1.15:1 typical 1000-3000 MHz |
| Insertion Loss | 0.10 dB/foot typical @ 500 MHz 0.15 dB/foot typical @ 1000 MHz 0.22 dB/foot typical @ 2000 MHz 0.27 dB/foot typical @ 3000 MHz |
| RF Input Power | 550 Watts average @ 500 MHz 350 Watts average @ 1000 MHz 250 Watts average @ 2000 MHz 185 Watts average @ 3000 MHz |
| Physical Size | See outline drawing 092-6371 |

| ECR/ECN # | DATE | REV | APPR / DATE | ECR/ECN # | DATE | REV | APPR / DATE |
|-----------|------------|-----|----------------|-----------|------|-----|-------------|
| | 11/16/2009 | | TRS 11/16/2009 | | | | |
| 21648 | 06/13/2012 | A | TRS 06/13/2012 | | | | |