


| CONNECTOR      | DIM. A $\pm .03$ |
|----------------|------------------|
| SMA MALE       | .56              |
| SMA FEMALE     | .52              |
| BNC MALE       | .80              |
| BNC FEMALE     | .60              |
| TNC MALE       | .80              |
| TNC FEMALE     | .60              |
| N MALE         | .96              |
| N FEMALE       | .73              |
| 7/16 MALE      | 1.31             |
| 7/16 FEMALE    | 1.22             |
| 4.1/9.5 MALE   | .96              |
| 4.1/9.5 FEMALE | .96              |
| 4.3/10 MALE    | 1.06             |
| 4.3/10 FEMALE  | 1.02             |

NOTE: MALE END TO BE MARKED WITH JFW MODEL NUMBER,  
ATTEN. VALUE, AND POWER RATING

| REV | ECN    | DATE      | BY  | APPR |  <b>JFW INDUSTRIES, INC.</b><br><a href="http://www.jfwindustries.com">www.jfwindustries.com</a> PH: 317-887-1340 |  |  |
|-----|--------|-----------|-----|------|--|--|--|
| -   | ISSUED | 3-16-98   | —   | —    |  |  |  |
| A   | 6050   | 7-1-99    | PT  | TEZ  | MATERIAL      ALUMINUM ALLOY<br>FINISH      BLACK ANODIZE  |  |  |
| B   | 6964   | 12-27-01  | MAH | TEZ  |  |  |  |
| C   | 7477   | 4-23-03   | CJW | TEZ  | MODEL      SCALE      FULL<br>DESCRIPTION      20 WATT FIXED ATTENUATOR  |  |  |
| D   | 7738   | 2-11-04   | TEZ | TEZ  |  |  |  |
| E   | 7900   | 6-23-04   | RLT | TEZ  | TOLERANCES<br>.XX $\pm$ .010 .XXX $\pm$ .005 XX $^{\circ}$ $\pm$ .5 $^{\circ}$   |  |  |
| F   | 12396  | 2-3-06    | BZ  | TEZ  |  |  |  |
| G   | 21671  | 6-21-12   | BZ  | TEZ  | DWG #      092-2759  |  |  |
| H   | 26009  | 12-14-15  | JZ  | TEZ  |  |  |  |
| J   | 24444  | 9-10-19   | GM  | JZ   |  |  |  |
| K   | 34042  | 3-24-2025 | JZ  | TRS  |  |  |  |
|     |        |           |     |      |  |  |  |
|     |        |           |     |      |  |  |  |
|     |        |           |     |      |  |  |  |