

-05
(i.e. 5 ATTENUATORS)

-04
(i.e. 4 ATTENUATORS)

-08
(i.e. 8 ATTENUATORS)

-03
(i.e. 3 ATTENUATORS)


-07
(i.e. 7 ATTENUATORS)

-02
(i.e. 2 ATTENUATORS)

-06
(i.e. 6 ATTENUATORS)

-01
(i.e. 1 ATTENUATORS)

PIN	FUNCTION
1	CHASSIS GROUND
2	RECEIVED DATA
3	TRANSMITTED DATA
4	NO CONNECTION
5	SIGNAL GROUND
6	NO CONNECTION
7	RTS
8	CTS
9	NO CONNECTION



CHASSIS DEPTH = 17.22 INCHES

NOTE:
ALL REAR PANELS ARE SCREENED FOR EIGHT ATTENUATORS TO ALLOW FOR FUTURE EXPANSION. ONLY USED SECTIONS ARE SHOWN FOR CLARITY.

REV	ECN	DATE	BY	APPR	TR
-	ISSUED	5-6-20	DTS	TR	

JFW INDUSTRIES, INC.
www.jfwindustries.com PH: 317-887-1340

MATERIAL	ALUMINUM ALLOY	PROPRIETARY INFORMATION
FINISH	CHEMFILM TCP / FRONT: BLACK	ALL SURFACES ARE TO BE FREE OF BURRS, PITS, & SCRATCHES
MODEL	50PA-XXX-X	TOLERANCES XX±.010 XXX±.005 XX*±.5'
DESCRIPTION	PROGRAMMABLE ASSEMBLY	DWG # 092-9418-02