

SPECIFICATION SHEET**JFW MODEL 50BT-065****BIAS TAP**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	950-2150 MHz
Impedance	50 Ohms nominal
VSWR (RF)	1.3:1 maximum (950-2150 MHz)
Insertion Loss (RF)	0.5 dB maximum (RF to RF+DC)
Insertion Loss (10MHz)	0.5 dB maximum (RF+DC to DC)
RF to DC/10MHz Isolation	20dB typical
DC Breakdown Voltage	100 Volts
DC Current Handling	1 Amp
RF Input Power	1 Watt average
RF Connector	SMA or N (male or female)
DC Connector	SMA or BNC female
Operating Temperature Range	-55°C to +85°C
Outline Drawing Numbers	092-5431 (SMA F/SMA F/SMA F) 092-5379 (N M/N F/BNC F) 092-7709 (SMA F/SMA F/BNC F) 092-10087 (N F/N F/BNC F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	05/21/2013		BAC 05/21/2013				
32695	07/07/2023	A	TRS 07/07/2023				