

SPECIFICATION SHEET
JFW MODEL 50C-067-XX
DIRECTIONAL COUPLER

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range 400-3000 MHz

Impedance 50 Ohms nominal

VSWR 1.3:1 maximum
1.2:1 typical

Coupling Values 10 dB $\pm$ 1.0 dB
20 dB $\pm$ 1.0 dB
30 dB $\pm$ 1.5 dB

Coupling Flatness $\pm$ 1.0 dB maximum
 $\pm$ 0.7 dB typical

Insertion Loss (including Coupling Loss) 10 dB: 1.1 dB maximum
0.8 dB typical
20 dB: 0.6 dB maximum
0.3 dB typical
30 dB: 0.5 dB maximum
0.3 dB typical

Directivity 20 dB minimum
22 dB typical

RF Input Power 100 Watts average

RF Connector N female

Temperature Range -45°C to +85°C (operating)
-55°C to +125°C (storage)

Physical Size See outline drawing 092-9189

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	10/24/2018		TRS 10/24/2018				
30502	07/02/2020	A	TRS 07/02/2020				