

SPECIFICATION SHEET
JFW MODEL 50C-068-XX
DIRECTIONAL COUPLER

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	2-6 GHz
Impedance	50 Ohms nominal
VSWR	1.35:1 maximum 1.25:1 typical
Coupling Values	10 dB $\pm$ 1.0 dB 20 dB $\pm$ 1.0 dB 30 dB $\pm$ 1.0 dB
Coupling Flatness	$\pm$ 1.0 dB maximum $\pm$ 0.7 dB typical
Insertion Loss (including Coupling Loss)	10 dB: 1.1 dB maximum 0.8 dB typical 20 dB: 0.6 dB maximum 0.3 dB typical 30 dB: 0.6 dB maximum 0.3 dB typical
Directivity	20 dB minimum 22 dB typical
RF Input Power	50 Watts average
RF Connector	N female
Environmental	Meets IP54 standard
Temperature Range	-45°C to +85°C (operating) -55°C to +125°C (storage)
Physical Size	See outline drawing 092-9215

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	11/26/2018		TRS 11/26/2018				
29182	11/28/2018	A	TRS 11/28/2018				
29944	11/12/2019	B	TRS 11/12/2019				