

SPECIFICATION SHEET

JFW MODEL 50DB-002

DC BLOCK

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Description Inner Only DC Block

Frequency Range 50 KHz-1800 MHz

Impedance 50 Ohms nominal

VSWR 1.3:1 maximum

Insertion Loss 0.5 dB maximum

DC Breakdown Voltage 100 Volts

RF Input Power 2 Watts average

RF Connector BNC, N, SMA or TNC
(male or female)

Outline Drawing Numbers

092-233	(50DB-002 BNC)
092-180	(50DB-002 TNC)
092-1948	(50DB-002 N)
092-4941	(50DB-002 BNC F/TNC M)
092-6591	(50DB-002 N F/BNC M)
092-6592	(50DB-002 N M/BNC M)
092-8455	(50DB-002 BNC M/SMA F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
2589	02/14/2001	C		11916	09/28/2005	F	BAC 09/28/2005
3074	08/07/2002	D		25815	10/19/2015	G	TRS 10/19/2015
9999	10/14/2002	E	SL 10/14/2002	26756	06/20/2016	H	TRS 06/20/2016