

SPECIFICATION SHEET**JFW MODEL 50DR-122****DUAL ROTARY ATTENUATOR**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-100 MHz
Impedance	50 Ohms nominal
Attenuation Range	0-80 dB in 1 dB steps
VSWR	1.15:1 maximum
Insertion Loss	0.1 dB maximum
Attenuation Accuracy	± 0.1 dB (1-10dB steps) ± 0.2 dB (20-70dB steps)
RF Input Power	2 Watts average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	BNC, SMA or N female
Operating Temperature Range	-20°C to +85°C
Physical Size	See outline drawing 092-327-03 (N) 092-440-03 (SMA) 092-1513-03 (BNC)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	02/10/2010		TRS 02/10/2010				
31861	06/27/2022	A	TRS 06/27/2022				
31866	06/28/2022	B	TRS 06/28/2022				