

SPECIFICATION SHEET

JFW MODEL 50FHC-XXX-10

FIXED ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-4000 MHz (1-40 dB)
DC-3000 MHz (41-60 dB)

Impedance 50 Ohms nominal

Attenuation Values 1-60 dB in any 1 dB increment
(XXX) insert value

VSWR (1-40 dB) 1.15:1 maximum DC-1000 MHz
1.35:1 maximum 1000-4000 MHz
(41-60 dB) 1.15:1 maximum DC-1000 MHz
1.35:1 maximum 1000-3000 MHz

Attenuation Accuracy (1-20 dB)
± 0.25 dB DC-1000 MHz
± 0.50 dB 1000-4000 MHz
(21-30 dB)
± 0.50 dB DC-1000 MHz
± 0.75 dB 1000-4000 MHz
(31-40 dB)
± 2% DC-2000 MHz
± 3% 2000-4000 MHz
(41-60 dB)
± 2% DC-2000 MHz
± 3% 2000-3000 MHz

RF Input Power (bi-directional) 10 Watts average @ +25°C
Derate to 5 Watts @ +70°C

Peak Power 1000 Watts

RF Connector BNC, N, SMA, RPT, TNC, 4.1-9.5 or
4.3-10.0
(RPT = reverse polarity TNC)

Operating Temperature Range -55°C to +100°C

Physical Size See outline drawing 092-1879

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
24660	02/01/2017	D	CLK 02/01/2017	26024	12/14/2015	E	TRS 12/14/2015
24660	10/29/2014	C	CLK 10/29/2014	27851	06/07/2017	E	CLK 06/07/2017
26007	12/14/2015	D	CLK 12/14/2015	32782	08/18/2023	F	TRS 08/18/2023