

SPECIFICATION SHEET

JFW MODEL 50MS-435

SOLID STATE MATRIX SWITCH

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	1-18 GHz
Configuration	4 x 6 Non-Blocking Matrix (See block diagram 092-9965) (Unused input ports are self-terminating) (Unused output ports are reflective) (all ports are bi-directional) (the ADMIN password is located on rear panel)
Enclosure Type	19 inch rack mount @ 3RU high
Impedance	50 Ohms nominal
VSWR	2.5:1 maximum 1.8:1 typical
Insertion Loss	20.5 dB maximum 18.3 dB typical @ 18 GHz
Isolation	Input to Input - 70 dB minimum Input to Output - 70 dB minimum Output to Output - 18 dB minimum (If connected to same Input) Output to Output - 70 dB minimum (If connected to different Inputs)
RF Input Power	+30 dBm (IN ports) +27 dBm (OUT ports)
Switching Speed	100 nanoseconds (After command is received and processed) (3 millisecond typical processing time)
Manual Control	20-Button Keypad and LCD display (IP Address configurable via keypad) (Net mask configurable via keypad) (Gateway configurable via keypad) (Baud rate configurable via keypad)
Remote Control	Ethernet (DHCP, TCP/IP, 10/100, up to 12 users) RS-232 (up to 115200 Baud)

--CONTINUED--

SPECIFICATION SHEET

JFW MODEL 50MS-435

SOLID STATE MATRIX SWITCH

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Remote Commands

Matrix Commands:
Matrix, Set Input, Set Output, Read Input, Read Output, Read All Inputs, Read All Outputs, Read Matrix Paths

System Commands:
Help, Identification, Store, Recall, Pause, Net, Serial, Close, Disconnect, MOTD, Date, Message, Restrict, IDENT, Name, Show Users, Reboot, Uptime, Prompt

Startup/Default States
(configurable)

All ports off at startup (see MATRIX command)
DHCP enabled (see NET command)
4 Ethernet users (see NET command)
Prompts off (see PROMPT command)

All of these default settings can be changed by user. Unit can be configured for up to 12 Ethernet users.

RF Connectors

N female or SMA female

AC Supply

100-240 VAC @ 47-63 Hz

Operating Temperature Range

0°C to +50°C

Physical Size

See outline drawing 092-9964

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	10/31/2022		TRS 10/31/2022				