

SPECIFICATION SHEET**JFW MODEL 50PD-379****2 WAY RESISTIVE POWER DIVIDER**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-4000 MHz
Impedance	50 Ohms nominal
VSWR	1.50:1 maximum 1.25:1 typical
Insertion Loss	6 dB $\pm$ 0.75 dB
Amplitude Tracking	$\pm$ 0.75
RF Input Power	2 Watts average @ 25°C 100 Watts peak (1 microsecond)
RF Connector*	BNC, N or TNC (male or female)
Physical Size	See outline drawing 092-2328-02 (N) 092-6646-02 (BNC) 092-5294 (NF/NM/SF) 092-5860 (N M/F/F)

* Note: For SMA female use JFW model 50PD-016 SMA.
It has a smaller enclosure and is a stocked model.

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
13792	01/23/2007	B	TRS 01/23/2007	22906	06/05/2013	E	TRS 06/05/2013
16317	09/17/2008	C	TRS 09/17/2008	30297	03/24/2020	F	TRS 03/24/2020
18885	07/15/2010	D	TRS 07/15/2010	31756	04/29/2022	G	TRS 04/29/2022