

**SPECIFICATION SHEET**

**JFW MODEL 50PD-560**

**4 WAY REACTIVE POWER DIVIDER/COMBINER**

JFW Industries, Inc.  
Phone: 317-887-1340  
sales@jfwindustries.com  
www.jfwindustries.com

Frequency Range	800-2400 MHz
Impedance	50 Ohms nominal
VSWR	1.4:1 maximum 1.2:1 typical
Insertion Loss (above 6 dB split)	0.8 dB maximum 0.28 dB typical @ 800 MHz 0.58 dB typical @ 2400 MHz
Amplitude Tracking	± 0.4 dB maximum ± 0.06 dB typical
Phase Tracking	± 6° maximum ± 1.8° typical
Isolation	20 dB minimum > 23 dB typical
RF Input Power	5 Watts average (divider port) 0.3 Watts average (combiner ports)
Operating Temperature Range	-40°C to +85°C
RF Connector	SMA female
Physical Size	See outline drawing 092-4857

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	07/11/2005		BAC 07/11/2005				
19114	09/14/2010	A	TRS 09/14/2010				
29525	05/15/2019	B	TRS 05/15/2019				