

SPECIFICATION SHEET**JFW MODEL 50S-1801****1P4T REFLECTIVE SOLID STATE RF SWITCH**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	30-512 MHz
Configuration	1P4T Reflective
Impedance	50 Ohms nominal
VSWR	1.4:1 maximum
Insertion Loss	0.40 dB typical 30-100MHz 0.60 dB typical 100-512MHz 0.75 dB maximum 30-512MHz
Isolation	50 dB minimum
Switching Speed	20 microseconds max. / 12 microseconds typ. (50% TTL to 10% or 90% RF) 40 microseconds typ. (50% TTL to specified isolation)
RF Input Power	200 Watts average (Cold Switch) 500 Watts peak (1usec pulse) 20 Watts average (Hot Switch)
Control Logic (3 Lines)	TTL per 092-5238 TTL "Low" = (0-0.8Vdc) TTL "High" = (2.0-5.0Vdc) TTL current = ± 1.3 mA maximum
DC Supply	+15 Vdc @ 450 mA nominal and +5 Vdc @ 175 mA nominal
RF Connector	SMA, TNC or N female
DC Connector	Solder terminals
Operating Temperature Range	-20°C to +70°C
Storage Temperature Range	-55°C to +85°C
Physical Size	See outline drawing 092-5238

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	11/06/2008		BAC 11/06/2008				