

SPECIFICATION SHEET

JFW MODEL 50S-1876

1P2T SELF TERMINATING SOLID STATE RF SWITCH

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	20-6000 MHz
Configuration	1P2T Self Terminating
Impedance	50 Ohms nominal
VSWR	1.25:1 typical 20-2000MHz 1.50:1 typical 2000-6000MHz 1.80:1 maximum 20-6000MHz
Insertion Loss	1.25 dB typical 20-2000 MHz 1.75 dB typical 2000-6000 MHz 2.50 dB maximum 20-6000 MHz
Isolation	75 dB typical 20-2000 MHz 70 dB typical 2000-4000 MHz 65 dB typical 4000-6000 MHz 55 dB minimum 20-6000 MHz
Switching Speed	10 microseconds maximum 5 microseconds typical (OFF-ON) 2 microseconds typical (ON-OFF) (50% TTL to 10% or 90% RF)
RF Input Power	+26 dBm average (Hot Switchable)
Control Logic (1 Lines)	TTL "Low" (0-0.8 Vdc) for COM to J1 and J2 Terminated TTL "High" (2.0-5.0 Vdc) for COM to J2 and J1 terminated
DC Supply	+5 Vdc @ 10 mA nominal
DC Connector	4 Pin (MOLEX #22-11-2042) Mating Connector: (MOLEX #22-01-3047)
RF Connector	SMA female
Operating Temperature Range	-40°C to +85°C
Storage Temperature Range	-55°C to +90°C
Physical Size	See outline drawing 092-6533

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	10/20/2010		BAC 10/20/2010				
19647	01/28/2011	A	BAC 01/28/2011				