

SPECIFICATION SHEET**JFW MODEL 50S-1972****1P8T SELF TERMINATING SOLID STATE RF SWITCH**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range 5-3000 MHz

Configuration 1P8T Self Terminating

Impedance 50 Ohms nominal

VSWR 1.3:1 typical 5-3000MHz
1.5:1 maximum 5-3000MHz

Insertion Loss 2.5 dB typical 5-3000MHz
3.5 dB maximum 5-3000MHz

Isolation 80 dB minimum 5-1000 MHz
70 dB minimum 1000-2000 MHz
60 dB minimum 2000-3000 MHz

Switching Speed 10 microseconds
(50% TTL to 10% or 90% RF)

RF Input Power +10 dBm average 5-20MHz
+20 dBm average 20-100 MHz
+30 dBm average 100-3000 MHz

Control Logic (4 Lines) Binary coded per 092-3658
TTL "High" (2.0-5.0V)
TTL "Low" (0-0.8V)

DC Supply +5 Vdc @ 100 mA nominal
and
+24 Vdc @ 300 mA nominal

Repeatability ± 0.05 dB typical

MTBF 226,017 hours

DC Connector 10 Pin 3M #3793-5303
(mates with 3M #3473-7010)

RF Connector SMA female

Operating Temperature Range 0°C to +70°C

Storage Temperature Range -55°C to +90°C

Physical Size See outline drawing 092-3658

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	03/19/2012		BAC 03/19/2012	24968	02/19/2015	C	TRS 02/19/2015
21673	06/21/2012	A	CLK 06/21/2012				
24944	02/17/2015	B	TRS 02/17/2015				