

**SPECIFICATION SHEET**  
**JFW MODEL 50T-133-XXX**  
**TERMINATION/MISMATCH**

JFW Industries, Inc.  
 Phone: 317-887-1340  
 sales@jfwindustries.com  
 www.jfwindustries.com

Available VSWR Values	1.0:1 thru 5.0:1 in any 0.1 increment (1.0:1 = termination)
Frequency Range	DC-1000 MHz (1.0:1 through 1.5:1) DC-100 MHz (1.6:1 through 5.0:1)
Impedance	50 Ohms (referenced)
VSWR Tolerance (Termination)	1.1:1 maximum (50T-133-1.0)
VSWR Tolerance (Mismatches)	± 5% from mismatch value
RF Input Power	200 Watts average @ +25°C Derated to 100 Watts @ +100°C
Peak Power	2500 Watts (100 microsecond pulse, 8% duty cycle)
RF Connector	N, BNC, TNC or 7/16 (male or female)
Physical Size	See outline drawing 092-1585 (N male)

XXX - Insert VSWR value required.  
 Other values available upon request.

Example Model Numbers:

50T-133-1.0 N M	Termination (1.0:1) with N male
50T-133-1.5 N F	1.5:1 mismatch with N female
50T-133-3.2 TNC F	3.2:1 mismatch with TNC female
50T-133-5.0 BNC F	5.0:1 mismatch with BNC female
50T-133-5.0 7/16 M	5.0:1 mismatch with 7/16 male

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
795	07/30/1997	A		9999	02/14/2003	C	SL 04/24/2003
975	02/24/1998	B		23288	09/30/2013	E	TRS 09/30/2013
4592	05/04/2004	D	CLV 05/04/2004				