

SPECIFICATION SHEET**JFW MODEL 50T-532****TERMINATION**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-3000 MHz

Impedance 50 Ohms

VSWR (Tolerance) 1.10:1 maximum DC-1000 MHz
1.20:1 maximum 1000-3000 MHz

RF Input Power 50 Watts average @ +25°C
derate to 25 Watts @ +85°C

Peak Power 1000 Watts

RF Connector BNC, N, TNC, SMA, 4.1-9.5, 4.3-10 or 7/16
(male or female)

Operating Temperature Range -55°C to +100°C

Outline Drawing Numbers 092-303-01 (BNC male)
092-303-02 (BNC female)
092-303-03 (N male)
092-303-04 (N female)
092-303-05 (TNC male)
092-303-06 (TNC female)
092-303-07 (SMA male)
092-303-08 (SMA female)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	03/29/2010	O	SMR 03/29/2010	27323	12/07/2016	C	TRS 12/07/2016
20453	08/12/2011	A	TRS 08/12/2011	34011	03/06/2025	D	TRS 03/06/2025
20536	09/06/2011	B	TRS 09/06/2011				