

SPECIFICATION SHEET

JFW MODEL 50T-713

TERMINATION

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-8.4 GHz

Impedance 50 Ohms nominal

VSWR 1.35:1 maximum
1.16:1 typical @ 8.4 GHz

RF Input Power 50 Watts average @ +25°C
Derated linearly to 0 Watt @ +125°C

Peak Power 1000 Watts
(5 microsecond pulse, 0.1% duty cycle)

RF Connector N or SMA
(male or female)

Temperature Range -55°C to +125°C

Optional Mounting Bracket Add "-MBK" to end of model number if you want the
optional mounting brackets included

Outline Drawing Numbers 092-10185-01 (N male)
092-10185-02 (N male with mounting brackets)
092-10185-03 (N female)
092-10185-04 (N female with mounting brackets)

Example model numbers:

50T-713 N M (N male)
 50T-713 N F (N female)
 50T-713 SMA M (SMA male)
 50T-713 SMA F (SMA female)

50T-713 N M-MBK (N male with optional mounting brackets)
 50T-713 N F-MBK (N female with optional mounting brackets)
 50T-713 SMA M-MBK (SMA male with optional mounting brackets)
 50T-713 SMA F-MBK (SMA female with optional mounting brackets)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	11/02/2023		TRS 11/02/2023				