

SPECIFICATION SHEET**JFW MODEL 75BR-024****BENCH TOP ROTARY ATTENUATOR**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Description	Manual attenuator mounted to L-bracket for benchtop usage
Frequency Range	DC-1000 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-70 dB in 1 dB steps
VSWR	1.5:1 maximum
Insertion Loss	0.8 dB maximum
Attenuation Accuracy (whichever is greater)	± 0.5 dB (1 dB steps) ± 0.5 dB or 3% (10 dB steps)
RF Input Power	1 Watt average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	BNC, F or N female
Operating Temperature Range	-20°C to +85°C
Lifetime	500,000 attenuation steps (each knob)
Physical Size	See outline drawing 092-4748

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	03/15/2005		BAC 03/15/2005				
28157	10/05/2017	A	TRS 10/05/2017				
33650	09/18/2024	B	TRS 09/18/2024				