

SPECIFICATION SHEET

JFW MODEL 75BR-036

BENCH TOP ROTARY ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-1218 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-70.75 dB in 0.25 dB steps
VSWR	1.7:1 maximum
Attenuation Accuracy	± 0.15 (0.25 dB steps) ± 0.5 (1 dB steps) ± 0.5 or 3% (10 dB steps)
Insertion Loss	3.4 dB maximum 2.4 dB typical
RF Input Power	1 Watt average 1000 Watts peak
Indexing	30 degrees with stops at minimum and maximum
RF Connector	F female
Operating Temperature Range	-20°C to +85°C
Lifetime	500,000 attenuation steps (each knob)
Physical Size	See outline drawing 092-8316

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	05/11/2015		TRS 05/11/2015	32940	10/24/2023	C	TRS 10/24/2023
25653	08/12/2015	A	TRS 08/12/2015				
28157	10/05/2017	B	TRS 10/05/2017				