

SPECIFICATION SHEET

JFW MODEL 75DR-029

DUAL ROTARY ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-1218 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-80 dB in 1 dB steps
VSWR	1.5:1 maximum DC-500 MHz 1.6:1 maximum 500-1218 MHz
Insertion Loss	0.9 dB maximum 0.6 dB typical @ 1218 MHz
Attenuation Accuracy	± 0.5 dB (1 dB steps) ± 1.0 dB (10 dB steps)
RF Input Power	1 Watt average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	30 degrees with stops at minimum and maximum
RF Connector	BNC, F or N female
Operating Temperature Range	-20°C to +85°C
Lifetime	500,000 attenuation steps (each knob)
Knob/Panel Mounting Drawing	092-8435-02
Outline Drawing Number	092-1513-03 (75DR-029 BNC)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	03/29/2016		TRS 03/29/2016				
27487	01/17/2017	A	TRS 01/17/2017				
28157	10/05/2017	B	TRS 10/05/2017				