SPECIFICATION SHEET

JFW MODEL 75FP-XXX-2G (1-20 DB)

FIXED ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-2000 MHz
Impedance	75 Ohms nominal
Attenuation Values	1 through 20 dB in 1 dB increments
VSWR	1.2:1 maximum @ 500 MHz 1.3:1 maximum @ 1000 MHz 1.4:1 maximum @ 2000 MHz
Attenuation Accuracy	± 0.3 dB DC-1000 MHz ± 0.5 dB or 3% 1000-2000 MHz
Peak Power	1 Watts @ +25°C
RF Connector	BNC, TNC, N or F
Physical Size	See outline drawing 092-233 (BNC) 092-164 (N) 092-180 (TNC) 092-2198 (F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	06/06/1990		SMR 03/04/2009	9999	08/25/2003	C	SMR 03/04/2009
43	10/21/1992	A	SMR 03/04/2009	16910	03/04/2009	D	SMR 03/04/2009
849	10/01/1997	B	SMR 03/04/2009				