

SPECIFICATION SHEET

JFW MODEL 75S-267

**1P2T FAILSAFE SELF TERMINATING ELECTROMECHANICAL
RF SWITCH**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-1450 MHz
Configuration	1P2T Failsafe Self Terminating
Impedance	75 Ohms nominal
VSWR	1.3:1 maximum to 500 MHz 1.5:1 maximum to 1450 MHz
Insertion Loss	0.5 dB maximum
Isolation	50 dB minimum to 500 MHz 45 dB minimum to 1450 MHz
Switching Speed	10 milliseconds maximum
RF Input Power	+20 dBm
DC Supply	+12 Vdc @ 50 mA nominal
Control (1 Line)	TTL "Low" J1 to J2 TTL "High" J1 to J3
DC Connector	Solder Terminals
RF Connector	BNC, F or N female or SMB male
Operating Temperature Range	-20°C to +85°C
Physical Size	See outline drawing 092-4430

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	03/17/2004		BAC 03/19/2004				
22219	12/06/2012	A	BAC 12/06/2012				