

SPECIFICATION SHEET**JFW MODEL 75S-303****1P16T FAILSAFE SELF TERMINATING
ELECTROMECHANICAL RF SWITCH**JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-2150 MHz
Configuration	1P16T Failsafe Self Terminating (failsafe to port J1)
Impedance	75 Ohms nominal
VSWR	1.5:1 maximum
Insertion Loss	0.50dB typical DC-1000MHz 0.75dB maximum DC-1000MHz 1.00dB typical 1000-2150MHz 1.50dB maximum 1000-2150MHz
Isolation	70 dB minimum to 1000 MHz 50 dB minimum to 2150 MHz
Switching Speed	10 milliseconds maximum
RF Input Power	+27 dBm maximum (limited by self-termination)
Control Logic (4 Lines)	TTL per 092-3394
DC Supply	+12 Vdc @ 50 mA nominal
DC Connector	DB-9P
RF Connector	BNC or F female
Operating Temperature Range	-20°C to +85°C
Physical Size	See outline drawing 092-3394

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	10/13/2009		BAC 10/13/2009				
18897	07/21/2010	A	TRS 07/21/2010				