

SPECIFICATION SHEET**JFW MODEL 75S-333****1P4T SELF TERMINATING SOLID STATE RF SWITCH**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	950-2150 MHz
Configuration	1P4T Self Terminating
Impedance	75 Ohms nominal
VSWR	1.3:1 typical 1.4:1 maximum
Insertion Loss	2.0 dB typical 2.5 dB maximum
Isolation	80 dB typical 70 dB minimum
Switching Speed	10 microseconds (50% TTL to 10% or 90% RF)
RF Input Power	+30 dBm average
Control Logic (4 Lines)	TTL "High" (2.0-5.0V) for ON TTL "Low" (0-0.8V) for OFF and internally terminated in 75 Ohms
DC Supply	+12 Vdc @ 200 mA nominal
RF Connector	F female
Operating Temperature Range	0°C to +70°C
Storage Temperature Range	-55°C to +90°C
Physical Size	See outline drawing 092-6904

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	03/22/2011		BAC 03/22/2011				
20338	07/15/2011	A	TRS 07/15/2011				