

SPECIFICATION SHEET

JFW MODEL 75SA-029

SWITCH ASSEMBLY

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-2150 MHz
Configuration	1P8T Failsafe Self Terminating
Impedance	75 Ohms nominal
VSWR	1.6:1 maximum
Insertion Loss	1.25 dB maximum DC-1000 MHz 2.50 dB maximum 1000-2150 MHz
Isolation	60 dB minimum DC-500 MHz 50 dB minimum 500-2150 MHz
RF Input Power	+24 dBm
Switching Speed	10 milliseconds
Remote Control	GPIB
Manual Control	Rotary switch
AC Supply	85-264VAC @ 47-63 Hz
RF Connector	BNC or F female
Control Connector	IEEE-488
Operating Temperature Range	0° to +70° C
Physical Size	See outline drawing 092-4869 (BNC) 092-4900 (F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	07/15/2005		BAC 07/18/2005				
11621	08/02/2005	A	TRS 08/02/2005				
11717	08/17/2005	B	BAC 08/17/2005				